

NW2203GCMM



- 3 needle, flatbed, bottom cover-stitch, belt-loop making machine with front fabric knife and 2 spreader 6 thread smocking mechanism
- ① The support (front) presser foot is independent against the main presser foot, so it is easy to remove, and it has a stoper to keep the lifted position. Therefore, it is easy to insert the fabric when starting the operation.
- ② Equipped with adjusting dials, both spring pressure of right and left lower knives can be equally adjusted.
- 3 Adjusting knob enables the machine to produce belt-loop from 8mm up to 20mm.
- *For the width over 16mm, the special wide needle plate and feed dogs are needed.

Features



Design of the smocking can be easily changed from backside of the machine by changing the cam, changing thread variation

more than 20 cams are available.



The machine has 2 spreaders and each spreader has 3thread eyelets. Design can be changed by variation of threads combination.



Model Name	Application	Material	Needle	No. of threads	Needle gauge	Needle bar stroke	Stitch length	Diff.Feed ratio	Presser foot lift	Maximum Speed
	7	₿	1		↓ → +		→ → inch	<u> </u>	<u>‡mm</u>	∭. s.p.m
NW2203GCMM	Belt loop	Medium to Heavy	UY X 128GAS 16	10	1/4"	31	2.1-4.2mm	N/A	6	2000

