

Safety stitch overlock machine with top feed mechanism

JJT3000



JJT3000 comes with general features of JJ3000 overlock such as DLC needle bar and looper holder, and oil return system on the needle bar to prevent oil leakage and perform in higher speed.

* JJT3116GE-03XK machines come with an angled knife for extra heavy materials. This knife cuts the fabric precisely and helps pushing down the cut fabric down.

Features

DLC(Diamond Like Carbon) needle bar and upper looper holder
Ensure durability and reliability. The machine can work in high speed and can work without any maintenance due to this mechanism.

Needle bar oil suction system

Protects the fabric from oil stains by soaking and sucking the extra oil on the needle bar surface.

Optional devices

Horizontal chain cutter(flat type), vacuum device, presser foot lifter, and direct drive motor are available on request for labor cost saving and the efficient operation.



Model	Fabric weight	Needle type	No. of Needles	Needle Space (mm)	Overedge Width (mm)	Stitch Length (mm)	Diff. Feed Ratio	Top feed Front-back (mm)	Top feed Up-down (mm)	Needle bar Stroke (mm)	Presser Foot lift (mm)	Max Speed (rpm)
JJT3014GH-01M-2X4	Medium	DCx27 #9	2	2	4	3.8	0.7~2	1~6	4.5	24.4	5.5	6700
JJT3014GE-40H-2X4	Heavy	DCx27 #11	2	2	4	2.4	1.1~3.8	1~8	5.5	24.4	6	6300
JJT3116GS-01M-3X4	Medium	DCx27 #11	2	3	4	3.8	0.7~2	1~6	3.5	24.4	5	7000
JJT3116GE-03XK-5X5	Extra heavy	DCx27 #21	2	5	5	5	0.8~1.5	1~7	5.5	26	7	6300
JJT3116GE-03XK-5X6	Extra heavy	DCx27 #21	2	5	6	5	0.8~1.5	1~7	5.5	26	7	6300
JJT3143GH-90M-3X2X4	Medium	DCx27 #11	3	3x2	4	3.8	0.7~2	1~6	4.5	26	5.5	6700