


NW8803GEK




3 needle, flatbed, high speed, top and bottom cover stitch machine with right side fabric cutter

* The machine in the left picture is equipped with optional devices 'MK-1' and 'direct drive motor'.



FRONT





Right side fabric trimmer The fabric cutter trims the right side of fabric in order to arranged the fabric edge to the right needle



Optional metering device

'MK-1' metering device can be attached in order to insert the elastic tape stably. also, since the 'MK-1'device reads the signal from the motor encoder, using 'Direct drive motor' is recommended.



Needle bar stroke Can be changed with a flat head screwdriver from 31mm to 33mm easily.

DLC coated needle bar A DLC(Diamond Like Carbon) coated needle bar ensures durability and reliability.



New oil seal The needle bar and the presser foot bar are equipped with the new oil seal that protects your product from oil stains.

Model Name	Application	Material	Needle	No. of threads	Needle gauge	Needle bar stroke	Stitch length	Diff.Feed ratio	Presser foot lift	Maximum Speed
	7	₿	1	, ZEZZ			→ → _{inch}	## ###	<u>‡mm</u>	€ s.p.m
NW8803GEK	Top & bottom covering	Light to medium	UY128GAS #10-14	5	7/32, 1/4	31mm	8~16 stitch/inch	0.7-2	5mm	5000