

JJ Series



One needle to three needles, overlock, tape attaching, safety stitch machines are available. Features are as below.

1. Fully sealed needle bar drive mechanism to prevent oil leak
2. Equipped with needle cooler & thread cooler
3. Low vibration / low noise design
4. Capable of high speed operation
5. Electricity saving direct drive servo motor is available

Variety of option devices are available for the productivity.

Features of the machine



Needle bar oil seal is applied

This mechanism protects the fabric from the oil stain



Diamond Like Carbon(DLC) coated needle bar and upper looper holder

Ensure durability and reliability and help machines run in high speed




JJ3014GH-40M-2X4

2-needle, standard overlock machine for attaching tape on T shirt shoulder, the machine comes with bracket for the tape



JJ3004GS-20F-1

1-needle overlock machine for turn-down hemming, for handkerchief and etc.



JJ3116GE-03X-5X6












2-needle safety overlock stitch machine for heavy denim, equipped with tractor presser foot



JJ3116GS-01H-5X5

2-needle safety stitch machine for shirts

Features of the machine

Subclass	Application	Fabric Weight	Type of Needle	No. of needles	No. of threads	Needle Space	Over edge width (mm)	Stitch length (mm)	Diff. feed ratio	Presser foot lift (mm)	Max Speed	Remarks
												
Standard overlock												
JJ3004GS-01M-4	plain seaming	light to medium	#9	1	3	-	4	1~3.8	0.7~2	5	8500	
JJ3005GS-10M-3	Hemming	light to medium	#9	1	3	-	3	1~3.8	0.7~2	5.5	8500	
JJ3005GS-10M-4	Hemming	light to medium	#9	1	3	-	4	1~3.8	0.7~2	5.5	8500	
JJ3004GS-20F-1	turn down Hemming	light to medium	#11	1	3	-	1.5	1~3.2	0.7~2	5	8500	
JJ3004GS-50M-3	manual backlatching	light to medium	#9	1	3	-	3	1~3.8	0.7~2	5	8500	
JJ3004GS-50M-4	manual backlatching	light to medium	#9	1	3	-	4	1~3.8	0.7~2	5	8500	
JJ3014GH-01M-2X3	plain seaming	light to medium	#9	2	4	2	3	1~3.8	0.7~2	5.5	7500	
JJ3014GH-01M-2X4	plain seaming	light to medium	#9	2	4	2	4	1~3.8	0.7~2	5.5	7500	
JJ3014GH-01M-2X5	plain seaming	light to medium	#9	2	4	2	5	1~3.8	0.7~2	5.5	7500	
JJ3014GH-40M-2X4	tape binding	light to medium	#9	2	4	2	4	1~3.2	0.7~2.4	5.5	7500	
JJ3014GH-40M-2X5	tape binding	light to medium	#9	2	4	2	5	1~3.2	0.7~2.4	5.5	7500	
JJ3014GH-50M-2X4	manual backlatching	light to medium	#9	2	4	2	4	1~3.8	0.7~2	5.5	7500	
JJ3014GH-50M-2X5	manual backlatching	light to medium	#9	2	4	2	5	1~3.8	0.7~2	5.5	7500	
Safety stitch overlock												
JJ3116GS-01M-3X4	plain seaming	light to medium	#11	2	5	3	4	1~3.8	0.7~2	5	7500	
JJ3116GS-01H-3X5	plain seaming	heavy	#14	2	5	3	5	1~3.8	0.7~2	5	7500	
JJ3116GS-01H-5X5	plain seaming	heavy	#14	2	5	5	5	1~3.8	0.7~2	5	7500	
JJ3116GH-01H-3X4	plain seaming	heavy	#14	2	5	3	4	1~3.8	0.7~2	5.5	7000	
JJ3116GH-01H-5X5	plain seaming	heavy	#14	2	5	5	5	1~3.8	0.7~2	5.5	7000	
JJ3116GE-03X-5X5	plain seaming	ultra heavy	#21	2	5	5	5	1~5	0.8~1.5	7	6500	tractor foot
JJ3116GE-03X-5X6	plain seaming	ultra heavy	#21	2	5	5	6	1~5	0.8~1.5	7	6500	tractor foot
JJ3116GE-03X-5X7	plain seaming	ultra heavy	#21	2	5	5	7	1~5	0.8~1.5	7	6500	tractor foot
JJ3116GS-30M-3X4	gathering	light to medium	#14	2	5	3	4	1~3.2	0.85~2.8	5	7000	
JJ3116GS-30M-5X5	gathering	light to medium	#14	2	5	5	5	1~3.2	0.85~2.8	5	7000	
JJ3116GS-30MP-3X4	gathering, piping	light to medium	#14	2	5	3	4	1~3.2	0.85~2.8	5	7000	
JJ3116GS-02M-3X4	plain seaming	light to medium	#11	2	5	3	4	1~3.8	0.7~2	5	7500	foot for tubular Structure
JJ3143GH-90M-3X2X4	plain seaming	light to medium	#11	3	6	3X2	4	1~3.8	0.7~2	5.5	7000	multi purpose

