

NR9803GALK-UTA




3 needle cylinder bed, top and bottom cover-stitch machine with left side fabric knife and suction device and pneumatic thread trimmer and presser foot lifter for hemming



*Application : T-shirt bottom hemming machine


Features



Adjustable needle bar stroke (31 or 33mm) for different thickness of garments

DLC coated needle bar for oil leakage prevention, last in high speed operation

High-end oil seals on bushings for oil leakage prevention in high speed operation



Two types of presser foots are include in the purchase for sewing different garments





Pneumatic thread trimmer is equipped



Pneumatic presser foot lifter is equipped







The fabric knife made of super hard steel last longer and secure clean cut of the fabric.

The machine comes with the complementary knife for thick materials.






The air blower to fold the fabric to be cut, avoiding curl up, as well to help the excess fabric to flow into the pipe.

Optional devices

Auxiliary devices support operators to handle the machine easily. It can cut training cost and increase productivity.



ABH-1M Pneumatic hemming guide with knee switch. Hemming is folded by air-blower without handling.



ABH-2R Semi-automatic hemming device for T-shirts sleeves.

Model Name	Applicatio n	Material	Needle	No. of threads	Needle gauge	Needle bar stroke	Stitch length	Diff.Feed ratio	Presser foot lift	Maximum Speed
		$\boldsymbol{\vartheta}$	1	, SERVE	 - +	mm	→ → inch	######################################	<u> </u>	€ s.p.m
NR9803GALK-UTA	Knit	light to medium	UYx128GAS 10-14	5	7/32, 1/4	33	6-16	0.3-2.9	6	5500

Morimoto Mfg. Co., Ltd.