High speed overlock, safety stitch machines



JJ3004GS-20F



One needle overlock machines for turndown hemming, for handkerchief and etc. Features are as below.


1. Fully sealed needle bar drive mechanism to prevent oil leak

2. Equipped with needle cooler & thread cooler

3. Low vibration / low noise design

4. Capable of high speed operation 5. Electricity saving direct drive servo

motor is available Variety of option devices are available for the productivity.



Features



Needle bar oil seal is applied This mechanism protects the fabric from the oil stain



Diamond Like Carbon(DLC) coated needle bar and upper looper holder

Ensure durability and reliability and help machines run in hiah speed

					•						
Application	Material	Needle	No. of Threads	Gauge	Needle bar Stroke	Stitch length stitch	Seam width	Feed dog pitch	Differential Feed ratio	Presser Foot lift	Maximu m Speed
\mathbf{A}	ϑ	/		₽. →1. +-	mm		S	ţ		↓ mm	(() s.p.m
handkerchie f	Light to Medium	1	3	-	24.4 (mm)	1~3.2 (inch)	1.5 (mm)	- (mm)	0.7~2	5 (mm)	7000
oto Mfg. Co., Ltd.				 ∎3¥∎						Tel: (81)72-877-1221	

Morimo 1-4-17, Suna, Shijohnawate-City, Osaka 575-0001, Japan



You Tube : kansaispecialjapan



Fax: (81)72-878-9649 www.kansai-special.com Email: hqeigyo@kansai-special.com