Belt-loop maker for front trimmer and puller



NW2202GPC



2 needle, flatbed, bottom cover stitch, beltloop making machine with front trimmer and puller.

[B-2000C/BLX series] and [NW series], flatbed machines, have been fused together to create a new model of belt loop sewing machine!

It is easier to use and has reinforced oil leakage prevention.



Technical improvement

- 1. Hard chrome plating coated needle bar
- 2. Closed oil circulation mechanism
- 3. Oil seal protects oil leakage in stitching area
- 4. Lower vibration, lower sound
- 5. Stitch length can be adjusted by pushbutton

Features



1: The support(front) presser foot is independent from main presser foot, so it can be easily detached and also it has a stopping function to keep at lifting position.

Therefore, it is extremely easy for the positioning of folder when starting to saw.

2: Equipped with new adjusting dial of lower knives.

Both spring pressure of right and left lower knives can be equally adjusted by this dial.

3: Adjusting knob enables you to fine-tune the cutter easily and produce belt loops

from 8mm up to 20mm. For the width over 16mm, the special wide needle plate and feed are available.

The attachment folder size 12mm for 1/4" or 10mm for 7/32", 3/16

Fabric cutting size can be adjusted easily by knob



Front



BACK

XLoop size 8mm∼20mm

Model Name	Application	Material	Needle	No. of threads	Needle gauge	Needle bar stroke	Stitch length	Diff.Feed ratio	Presser foot lift	Maximum Speed
	7	$\boldsymbol{\vartheta}$	1	(SESSE)	↓ ↓		→ → _{inch}	### ###	<u>‡mm</u>	€ s.p.m
NW2202GPC	Belt loop	Medium to Heavy	UY X 128GAS 14-16	3	3/16,7/32, 1/4,1/4W"	31	6-12mm	N/A	8	4500



